



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the Product Covered described below herein when made in accordance with the authorized Listing Report, including Manufacturing/Machining Specifications, and under conditions set forth in the Certification Agreement and Listing Report, including Manufacturing/Machining Specifications. This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

Client Number: 55457

Report Number: 3108741

Evaluation Center:

Intertek (Coquitlam)

Applicant/Basic Listee:

Fox Blocks, a Division of Airlite Plastics Company
6110 Abbott Drive
Omaha, NE 68110-2805

Norman Rief
402-341-7300
402-408-5099

Product Covered:

Airlite Plastics Company - Fox Blocks ICF

Testing Standards:


ASTM D1929-96 (reapproved 2001) ASTM E84 (2005)
ASTM C578 (2003) ASTM D1761 (1988)

This document is the property of Intertek Testing Services and is not transferable. Only the Applicant may reproduce this document. The Certification Mark(s) may be applied only at the above noted location of the Party Authorized to Apply the Mark(s).



This document supersedes all previous Authorizations to Mark for the noted Report Number.

Authorized By: _____



Bob Davison, Certification Manager

Intertek Testing Services NA, Inc.
8431 Murphy Drive, Middleton, WI 53562 USA
Phone 608-824-7440 Fax 608-831-9279

Listing Section:

OTHER PRODUCTS

Description:

PRODUCT COVERED

Fox Blocks Insulating Concrete Forms (ICF)

PRODUCT DESCRIPTION

Fox Blocks ICF consists of expanded polystyrene (EPS) panels, which are held in place by polypropylene (PP) webs. There are 5 to 9 web types depending on the type of form being manufactured. The webs also have flanges on their ends for the full height of the forms, such that when they are in position in the EPS and in the finished wall, the flanges serve as continuous furring strips for attachment of interior and exterior finishes.

The Fox Blocks ICF currently come in three sizes: a 4-inch cavity, 6-inch cavity and 8-inch cavity allowing a 4-inch, 6-inch and 8-inch concrete wall system respectively. The forms are available in the following sizes:

4-, 6- and 8-inch Forms:

Straight
90 degree corner
45 degree corner

6- and 8-inch Forms:

Corbel ledge
Taper top
T-Block short leg
T-Block long leg

**Party Authorized To Apply
Mark:**

None